MATERIAL SAFETY DATA SHEET

This product is classified as a Non Hazardous Substance according to criteria of NOHSC Australia

1. IDENTIFICATION OF THE MATERIAL

Product Name:	Maxi Speed Filla Light		
Other Names;	Light filler		
Product Code:	JdSpg140 2Q		
Supplier:	GSB Chemical Co. Pty. Ltd	Telephone:	+61 03 9457 1125
	ACN 004 355113	Facsimile:	+61 03 9459 7978
	84 Camp Road	Internet:	www.gsbchem.com.au
	Broadmeadows Vic. 3047	e-mail:	info@gsbchem.com.au

Major Uses and Methods of Application: For filling cracks and holes in cement, bricks and wood. Refer to instructions on container for application details.

2. COMPOSITION

	CAS No.	PROPORTION
Silicon Dioxide	14808-60-7	30 - 60% w/w
Water	7732-18-5	<10% w/w
Barium Sulphate	7727-43-7	10 – 30% w/w
Acrylic polymer	Proprietary	30 - 60% w/w
Non ionic surfactants		< 1% w/w
Hydrocarbon antifoam		<1% w/w

3. HAZARDS IDENTIFICATION

Non Hazardous

4. FIRST AID MEASURES

For advice, contact a Poisons information Centre (Phone Australia 13 1126, New Zealand 0 800 764766)

Swallowed:	Do NOT induce vomiting. Give 1 – 3 glasses of water and seek medical attention
Eye:	Flush with flowing water for at least 15 minutes, and if symptoms persist, seek medical attention.
Skin:	Remove contaminated clothing, wash skin thoroughly with soap and water. Wash contaminated clothing before reuse. Seek medical advice if effects persist
Inhalation:	Blow nose. Clean nostrils with moist cotton wool. If irritation occurs due to prolonged or severe exposure seek medical advice
Advice to Doctor:	Treat symptomatically based on assessment by doctor and individual reactions of patient

5. FIRE FIGHTING MEASURES

Product will not support combustion. However, polymer will burn in a general fire, once all the water has been driven off. Products of combustion include carbon monoxide and carbon dioxide.
Use dry chemical, foam, CO_2 or water spray (fog).

6. ACCIDENTAL RELEASE MEASURES

Spilled product may make floors and surfaces slippery.
Shut off all sources of ignition, contain spill and recover spilled product for safe disposal. Remainder can be soaked into an inert absorbent (vermiculite, sand, etc.).

7. HANDLING AND STORAGE

Ensure containers are kept closed when not in use.
Store in a cool dry place away from heat.

8. EXPOSURE AND PERSONAL PROTECTION

None available

Personal Protection:

Eye protection:	Safety glasses, goggles or face shield as required
Hand Protection:	PVC, neoprene or nitrile rubber gloves
Footwear:	Rubber boots
Respiratory Protection:	Approved respirator, if required

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Heavy pliable putty
Boiling Point:	N/A
Specific Gravity:	~ 0.8
Flash Point:	Non flammable
Solubility in water:	insoluble

10. STABILITY AND REACTIVITY

Stable under ordinary conditions of use and storage. Ensure containers are kept closed when not in use. Avoid high temperatures; Linseed Oil is a combustible liquid. Do not use near ignition source. No smoking

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this MSDS and product label. Symptoms or effects that may arise if the product is misused and overexposure occurs are:

Swallowed:	Ingestion of large amounts may result in abdominal pain and discomfort
Eye:	Moderate irritant.
Skin:	Non irritant.
Inhalation:	High concentrations of the vapour are unlikely unless the product is fiercely heated. High concentrations may cause depression, dizziness, nausea, and headache. Irritation of mucous membranes and respiratory tract are possible. Aspiration (e.g. during vomiting) into the lungs can cause serious pneumonitis

12. ECOLOGICAL INFORMATION

Keep out of sewers, storm drains, surface waters and soil

13.DISPOSAL

For small spills, sweep up and dispose in approved waste container. Dispose collected and unrecoverable material to an approved site.
Contact local authority

14. TRANSPORT INFORMATION

Not classified as dangerous goods.

15. REGULATORY INFORMATION

Not applicable

16. OTHER INFORMATION

Contact: Technical Manager
Telephone (03) 94571125

The information and recommendations in this publication are to the best of our knowledge accurate at the time of publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or process. Nothing herein is to be construed as warranty, expressed or implied. In all cases, it is the responsibility of the user to determine the applicability of such information or the suitability of any products for their own particular use.

END OF MSDS