

KCB GUM TURPENTINE

Hazard Alert Code:
MODERATE

Chemwatch Material Safety Data Sheet (REVIEW)

Revision No: 2.0

Chemwatch 23-0381

Issue Date: 21-Feb-2010

CD 2010/1

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

KCB Gum Turpentine

SYNONYMS

"Wood Turpentine"

PROPER SHIPPING NAME

TURPENTINE

PRODUCT USE

■ Used according to manufacturer's directions. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Solvent for waxes, lacquers and paints, medicine and perfumery. Used in the manufacture of shoe stove and furniture polishes

SUPPLIER

Company: KCB Sales Pty Ltd

Address:

15 Production Street

Wacol

QLD, 4076

AUS

Telephone: +61 7 3271 2666

Fax: +61 7 3271 3667

Email: sales@kcbsales.com.au

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.

HAZARD RATINGS

	Min	Max
Flammability:	2	
Toxicity:	2	
Body Contact:	2	
Reactivity:	1	
Chronic:	2	

Min/Nil=0
Low=1
Moderate=2
High=3
Extreme=4



POISONS SCHEDULE

S5

RISK

- Flammable.
- Harmful by inhalation in contact with skin and if swallowed.
- Irritating to eyes and skin.
- May cause SENSITISATION by skin contact.
- Toxic to aquatic organisms may cause long-term adverse effects in the aquatic environment.
- HARMFUL - May cause lung damage if swallowed.
- Vapours may cause drowsiness and dizziness.
- May produce discomfort of the respiratory system*.
- Limited evidence of a carcinogenic effect*.
- Possible respiratory sensitiser*.
- Repeated exposure potentially causes skin dryness and cracking*.

SAFETY

- Do not breathe gas/ fumes/ vapour/ spray.
- Avoid contact with eyes.
- Wear suitable protective clothing.
- Use only in well ventilated areas.
- Keep container in a well ventilated place.
- To clean the floor and all objects contaminated by this material use water and detergent.
- Keep container tightly closed.
- This material and its container must be disposed of in a safe way.
- Keep away from food drink and animal feeding stuffs.
- In case of contact with eyes rinse with plenty of water and contact Doctor or Poisons Information Centre.
- If swallowed IMMEDIATELY contact Doctor or Poisons Information Centre (show this container or label).

KCB GUM TURPENTINE

Hazard Alert Code:
MODERATE

Chemwatch Material Safety Data Sheet (REVIEW)

Revision No: 2.0

Chemwatch 23-0381

Issue Date: 21-Feb-2010

CD 2010/1

* (limited evidence).

- Use appropriate container to avoid environment contamination.
- Avoid release to the environment. Refer to special instructions/safety data sheets.
- This material and its container must be disposed of as hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
gum turpentine	9005-90-7	>60

Section 4 - FIRST AID MEASURES

SWALLOWED

-
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.
- Avoid giving milk or oils.
- Avoid giving alcohol.
- If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

EYE

- If this product comes in contact with the eyes:
 - Wash out immediately with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Seek medical attention without delay; if pain persists or recurs seek medical attention.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
 - Immediately remove all contaminated clothing, including footwear.
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

-
- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

■ Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology]

KCB GUM TURPENTINE

Hazard Alert Code:
MODERATE

Chemwatch Material Safety Data Sheet (REVIEW)

Revision No: 2.0

Chemwatch 23-0381

Issue Date: 21-Feb-2010

CD 2010/1

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Do not use a water jet to fight fire.

FIRE FIGHTING

-
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

-
- Liquid and vapour are flammable.
- Moderate fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Moderate explosion hazard when exposed to heat or flame.
- Vapour may travel a considerable distance to source of ignition.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include: carbon monoxide (CO), carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.

FIRE INCOMPATIBILITY

-
- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

HAZCHEM

3Y

Personal Protective Equipment

Gas tight chemical resistant suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

-
- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Wipe up.
- Collect residues in a flammable waste container.

MAJOR SPILLS

■ CARE: Absorbent materials wetted with occluded oil must be moistened with water as they may auto-oxidize, become self heating and ignite.

Some oils slowly oxidise when spread in a film and oil on cloths, mops, absorbents may autoxidise and generate heat, smoulder, ignite and burn. In the workplace oily rags should be collected and immersed in water.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse /absorb vapour.
- Contain spill with sand, earth or vermiculite.

KCB GUM TURPENTINE

Hazard Alert Code:
MODERATE

Chemwatch Material Safety Data Sheet (REVIEW)

Revision No: 2.0


Chemwatch 23-0381

Issue Date: 21-Feb-2010

CD 2010/1

- Use only spark-free shovels and explosion proof equipment.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

PROTECTIVE ACTIONS FOR SPILL



FOOTNOTES

- 1 PROTECTIVE ACTION ZONE is defined as the area in which people are at risk of harmful exposure. This zone assumes that random changes in wind direction confines the vapour plume to an area within 30 degrees on either side of the predominant wind direction, resulting in a crosswind protective action distance equal to the downwind protective action distance.
- 2 PROTECTIVE ACTIONS should be initiated to the extent possible, beginning with those closest to the spill and working away from the site in the downwind direction. Within the protective action zone a level of vapour concentration may exist resulting in nearly all unprotected persons becoming incapacitated and unable to take protective action and/or incurring serious or irreversible health effects.
- 3 INITIAL ISOLATION ZONE is determined as an area, including upwind of the incident, within which a high probability of localised wind reversal may expose nearly all persons without appropriate protection to life-threatening concentrations of the material.
- 4 SMALL SPILLS involve a leaking package of 200 litres (55 US gallons) or less, such as a drum (jerrican or box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a small cylinder are also considered "small spills". LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.
- 5 Guide 128 is taken from the US DOT emergency response guide book.
- 6 IERG information is derived from CANUTEC - Transport Canada.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
 - Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- Contains low boiling substance:
Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.
- Check for bulging containers.
 - Vent periodically
 - Always release caps or seals slowly to ensure slow dissipation of vapours
 - DO NOT allow clothing wet with material to stay in contact with skin
 - Electrostatic discharge may be generated during pumping - this may result in fire.
 - Ensure electrical continuity by bonding and grounding (earthing) all equipment.
 - Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/sec until fill pipe submerged to twice its diameter, then ≤ 7 m/sec).
 - Avoid splash filling.
 - Do NOT use compressed air for filling discharging or handling operations.
 - Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of overexposure occurs.
 - Use in a well-ventilated area.
 - Prevent concentration in hollows and sumps.
 - DO NOT enter confined spaces until atmosphere has been checked.
 - Avoid smoking, naked lights or ignition sources.
 - Avoid generation of static electricity.
 - DO NOT use plastic buckets.
 - Earth all lines and equipment.
 - Use spark-free tools when handling.
 - Avoid contact with incompatible materials.

KCB GUM TURPENTINE

Hazard Alert Code:
MODERATE

Chemwatch Material Safety Data Sheet (REVIEW)

Revision No: 2.0

Chemwatch 23-0381

Issue Date: 21-Feb-2010

CD 2010/1

- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

SUITABLE CONTAINER

- Store in a dark glass or other suitable light resistant container.
- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C)
- (i) : Removable head packaging;
- (ii) : Cans with friction closures and
- (iii) : low pressure tubes and cartridges may be used.
- Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages
- In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.


STORAGE INCOMPATIBILITY

- d-Limonene:
 - forms unstable peroxides in storage, unless uninhibited; may polymerise
 - reacts with strong oxidisers and may explode or combust
 - is incompatible with strong acids, including acidic clays, peroxides, halogens, vinyl chloride and iodine pentafluoride
 - flow or agitation may generate electrostatic charges due to low conductivity
 - Avoid reaction with oxidising agents
- strong acids.
strong alkalis.
amines.

STORAGE REQUIREMENTS

- - Store in original containers in approved flammable liquid storage area.
 - Store away from incompatible materials in a cool, dry, well-ventilated area.
 - DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
 - No smoking, naked lights, heat or ignition sources.
 - Storage areas should be clearly identified, well illuminated, clear of obstruction and accessible only to trained and authorised personnel - adequate security must be provided so that unauthorised personnel do not have access.
 - Store according to applicable regulations for flammable materials for storage tanks, containers, piping, buildings, rooms, cabinets, allowable quantities and minimum storage distances.
 - Use non-sparking ventilation systems, approved explosion proof equipment and intrinsically safe electrical systems.
 - Have appropriate extinguishing capability in storage area (e.g. portable fire extinguishers - dry chemical, foam or carbon dioxide) and flammable gas detectors.
 - Keep adsorbents for leaks and spills readily available.
 - Protect containers against physical damage and check regularly for leaks.
 - Observe manufacturer's storing and handling recommendations.
- In addition, for tank storages (where appropriate):
- Store in grounded, properly designed and approved vessels and away from incompatible materials.
 - For bulk storages, consider use of floating roof or nitrogen blanketed vessels; where venting to atmosphere is possible, equip storage tank vents with flame arrestors; inspect tank vents during winter conditions for vapour/ ice build-up.
 - Storage tanks should be above ground and diked to hold entire contents.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



X: Must not be stored together

O: May be stored together with specific preventions

+: May be stored together

KCB GUM TURPENTINE

Hazard Alert Code:
MODERATE

Chemwatch Material Safety Data Sheet (REVIEW)

Revision No: 2.0

Chemwatch 23-0381

Issue Date: 21-Feb-2010

CD 2010/1

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
Australia Exposure Standards	gum turpentine (Turpentine (wood))	100	557						Sen

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m ³)	Revised IDLH Value (ppm)
gum turpentine		800

MATERIAL DATA

KCB GUM TURPENTINE:

■ for d-Limonene:

CEL TWA: 30 ppm, 165.6 mg/m³ (compare WEEL-TWA*)

A Workplace Environmental Exposure Level* has been established by AIHA (American Industrial Hygiene Association) who have produced the following rationale:

d-Limonene is not acutely toxic. In its pure form it is not a sensitiser but is irritating to the skin. Although there is clear evidence of carcinogenicity in male rats, the effect has been attributed to an alpha-2u-globin (a2u-G) renal toxicity which is both species and gender specific. Humans do not synthesise a2u-G, and metabolism studies indicate that 75% to 95% of d-limonene is excreted in 2-3 days with different metabolites identified between humans and rats. In a 2-year study, liver effects were noted in male mice at 500 mg/kg and reduced survival was noted in female rats at 600 mg/kg. The no observable effect levels (NOELs) were 250 and 300 mg/kg, respectively. A WEEL of 30 ppm is recommended to protect against these effects.

Turpentine is a skin and mucous irritant and skin contact has been associated with eczema. It also produces central nervous (CNS) depression.

The TLV-TWA is thought to be protective against upper respiratory tract irritation.

Human subjects exposed to 750 to 1000 ppm turpentine vapour complained of ocular irritation, headache, dizziness, nausea and tachycardia. Volunteers exposed to turpentine vapour for 3 to 5 minutes showed nose and throat irritation at 75 ppm whilst 175 ppm was intolerable for the majority. A majority of subjects estimated 100 ppm to be the highest concentration which could be tolerated for an 8 hour exposure.

GUM TURPENTINE:

■ for d-Limonene:

CEL TWA: 30 ppm, 165.6 mg/m³ (compare WEEL-TWA*)

A Workplace Environmental Exposure Level* has been established by AIHA (American Industrial Hygiene Association) who have produced the following rationale:

d-Limonene is not acutely toxic. In its pure form it is not a sensitiser but is irritating to the skin. Although there is clear evidence of carcinogenicity in male rats, the effect has been attributed to an alpha-2u-globin (a2u-G) renal toxicity which is both species and gender specific. Humans do not synthesise a2u-G, and metabolism studies indicate that 75% to 95% of d-limonene is excreted in 2-3 days with different metabolites identified between humans and rats. In a 2-year study, liver effects were noted in male mice at 500 mg/kg and reduced survival was noted in female rats at 600 mg/kg. The no observable effect levels (NOELs) were 250 and 300 mg/kg, respectively. A WEEL of 30 ppm is recommended to protect against these effects.

Turpentine is a skin and mucous irritant and skin contact has been associated with eczema. It also produces central nervous (CNS) depression.

The TLV-TWA is thought to be protective against upper respiratory tract irritation.

Human subjects exposed to 750 to 1000 ppm turpentine vapour complained of ocular irritation, headache, dizziness, nausea and tachycardia. Volunteers exposed to turpentine vapour for 3 to 5 minutes showed nose and throat irritation at 75 ppm whilst 175 ppm was intolerable for the majority. A majority of subjects estimated 100 ppm to be the highest concentration which could be tolerated for an 8 hour exposure.

PERSONAL PROTECTION



EYE

-
- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]

KCB GUM TURPENTINE

Hazard Alert Code:
MODERATE

Chemwatch Material Safety Data Sheet (REVIEW)

Revision No: 2.0

Chemwatch 23-0381

Issue Date: 21-Feb-2010

CD 2010/1

HANDS/FEET

-
- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

OTHER

-
- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets), non sparking safety footwear.

RESPIRATOR

■ Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half-face Respirator	Full-Face Respirator
1000	10	A-AUS	-
1000	50	-	A-AUS
5000	50	Airline *	-
5000	100	-	A-2
10000	100	-	A-3
	100+		Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

■ Care: Atmospheres in bulk storages and even apparently empty tanks may be hazardous by oxygen depletion. Atmosphere must be checked before entry.

Requirements of State Authorities concerning conditions for tank entry must be met. Particularly with regard to training of crews for tank entry; work permits; sampling of atmosphere; provision of rescue harness and protective gear as needed.

For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

KCB GUM TURPENTINE

Hazard Alert Code:
MODERATE

Chemwatch Material Safety Data Sheet (REVIEW)

Revision No: 2.0

Chemwatch 23-0381

Issue Date: 21-Feb-2010

CD 2010/1

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Colourless liquid with a penetrating odour; not miscible with water.

PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Floats on water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	155-170	Solubility in water (g/L)	Immiscible
Flash Point (°C)	32 (CC)	pH (1% solution)	Not Available
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Available
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	0.86
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

-
- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733).

KCB GUM TURPENTINE

Hazard Alert Code:
MODERATE

Chemwatch Material Safety Data Sheet (REVIEW)

Revision No: 2.0

Chemwatch 23-0381

Issue Date: 21-Feb-2010

CD 2010/1

Terpenes and their oxygen-containing counterparts, the terpenoids, produce a variety of physiological effects. Pine oil monoterpenes, for example, produce a haemorrhagic gastritis characterised by stomach pain and bleeding and vomiting. Systemic effects of pine oils include weakness and central nervous depression, excitement, loss of balance, headache, with hypothermia and respiratory failure.

The mean lethal oral dose ranges between 19 and 50 ml turpentine. Aspiration may cause pathognomonic dyspnea, acute pulmonary oedema, and cyanosis. Death occurs in central arrest. Acute turpentine poisoning has been associated with glucosuria, haematuria, albuminuria, and anuria.

EYE

■ This material can cause eye irritation and damage in some persons.

At 175 ppm turpentine vapour, eye irritation is evident. Direct liquid contact may produce blepharospasm, conjunctival hyperaemia, slight injury to the corneal epithelium, corneal burns and temporary erosion of the epithelium.

SKIN

■ Skin contact with the material may be harmful; systemic effects may result following absorption.

This material can cause inflammation of the skin on contact in some persons.

The material may accentuate any pre-existing dermatitis condition.

Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.

Open cuts, abraded or irritated skin should not be exposed to this material.

It is likely that older pine oils become irritants from the build up of peroxides of delta-3-carene and limonene etc.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Older preparations of turpentine are said to contain high concentrations of delta-carotene, a substance said to be responsible for eczema. Workers in the chemical, rubber and welding industries have developed contact dermatoses. Skin contact may produce erythema, eczema, itching, chemical burns and allergic sensitisation.

Essential oils irritate the skin and redden it, causing at first warmth and smarting, followed by some local loss of sensation. They have been used to treat chronic inflammatory conditions and to relieve neuralgia and rheumatic pain. Care should be taken to avoid blistering; these oils may also produce sensitisation.

INHALED

■ Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.

There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Inhalation hazard is increased at higher temperatures.

Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.

Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.

Signs of acute turpentine intoxication in rats include ataxia, tremour, convulsions, tachypnea, decreased tidal volume, and death due to sudden apnea. Turpentine components tend to concentrate in the spleen and brain. Occupational exposure to turpentine vapours include respiratory irritation, renal injury and deaths. Inhalation exposure to oil of turpentine at 75-175 ppm produces irritation of the nose and throat; at 750-1000 ppm, exposure for several hours produces headache, dizziness, nausea and tachycardia. Heavy overexposures produce coughing, choking, dyspnea, bronchitis, chest pain, burning, sensation in the mouth, throat, oesophagus and stomach, vomiting, diarrhoea, abdominal pain, painful urination with violet-like urine odour. Bladder and kidney irritation with haematuria, albuminuria and glycosuria. Central nervous system depression may occur after initial excitement, followed by ataxia, confusion, anorexia, stupor, tinnitus, hallucinations, distorted perceptions, antipsychotic changes, delayed convulsions, coma and death due to respiratory failure.

Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.

CHRONIC HEALTH EFFECTS

■ Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.

There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

In the presence of air, a number of common flavour and fragrance chemicals can form peroxides surprisingly fast. Antioxidants can in most cases minimise the oxidation.

Fragrance terpenes are generally easily oxidised in air. Non-oxidised limonene, linalool and caryophyllene turned out to be very weak sensitizers, however after oxidation limonene hydroperoxide and linalool hydroperoxide are strong sensitizers. Of the patients tested 2.6% showed positive reaction to oxidised limonene, 1.3% to oxidised linalool, 1.1% to linalool hydroperoxide, 0.5% to oxidised caryophyllene, while testing with caryophyllene oxide and oxidised myrcene resulted in few positive patch tests. 2/3 of the patients reacting positive to oxidised terpenes had fragrance related contact allergy and/or positive history for adverse reactions to fragrances.

As well as the hydroperoxides produced by linalol, limonene and delta-3-carene other oxidation and resinification effects progressively causes other fairly major changes in essential oil quality over time. Autoxidation of fragrance terpenes contributes greatly to fragrance allergy, which emphasizes the need of testing with compounds that patients are actually exposed to and not only with the ingredients originally applied in commercial formulations.

Essential oils and isolates derived from the Pinacea family, including Pinus and Abies genera, should only be used when the level of peroxides is kept to the lowest practicable level, for instance by adding antioxidants at the time of production. Such products should have a peroxide value of less than 10 millimoles peroxide per liter. Based on the published literature mentioning sensitising properties when containing peroxides (Food and Chemical Toxicology 11,1053(1973); 16,843(1978); 16,853(1978).

d-Limonene may cause damage to and growths in the kidney. These growths can progress to cancer.

Parenteral turpentine has been used as an abortifacient where it has induced peritonitis, pelvic necrosis, and inflammation, and pulmonary oedema. Repeated or prolonged exposure to oil of turpentine may produce cerebral atrophy, behavioural changes, anaemia and bone marrow injury, and glomerulonephritis.

TOXICITY AND IRRITATION

KCB GUM TURPENTINE**Hazard Alert Code:
MODERATE**

Chemwatch Material Safety Data Sheet (REVIEW)

Revision No: 2.0

Chemwatch 23-0381

Issue Date: 21-Feb-2010

CD 2010/1

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.
- Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

For bicyclic terpenes:

Acute toxicity: The literature abounds with clinical reports of accidental and intentional acute poisoning with pinene-based turpentine.

Rat oral LD50 values are available for alpha-pinene, beta-pinene, camphene and turpentine oil and indicate these materials to be very low in oral acute toxicity with LD50 values in the range from 3388 mg/kg to greater than 5000 mg/kg. Rabbit dermal LD50 values similarly indicate very low toxicities with values greater than the limit doses of 2000 or 5000 mg/kg.

Acute inhalation toxicity has been measured in different animal species. The acute LC50 was reported to be 13,500 mg/m³ in rats, 13,500 mg/m³ in guinea pigs, and 9000 mg/m³ in mice. The acute inhalation LC50 of commercial grade turpentine in Wistar rats is reported to be in the range of 12,000-20,000 mg/m³ for 1 to 6 hour exposures and the LC50 for a 2-hour exposure in Swiss-Webster mice is 29,000 mg/m³. Based on these results the acute oral, dermal, and inhalation toxicities of bicyclic terpene hydrocarbons is concluded to be low.

Repeat dose toxicity: A 28-day repeat dose study has been performed with camphene according to an OECD Guideline 407 in both sexes of Wistar rats. Animals of both sexes at the 1000 mg/kg bw/day dose exhibited vacuolization of hepatocytes and increase liver weights. Male rats also exhibited alpha-2-microglobulin-type nephrotoxicity at all dose levels.

Subsequent investigations have shown that the alpha-2-microglobulin nephropathy found in the F344/N male rat does not develop in mammals that do not express the hepatic form of alpha-2-microglobulin (e.g. other strains of rats, mice, dogs, humans). Therefore, the nephrotoxicity observed in the camphene study in male F344 rats is not relevant to the human health risk assessment. Based on liver toxicity, the NOAEL for this study is concluded to be 250 mg/kg bw/day

Reproductive toxicity: In the a-animal species study, no reproductive effects were observed when dose levels of up to 260 to 600 mg/kg bw of an essential oil predominantly composed of bicyclic terpene hydrocarbons (alpha-pinene, beta-pinene, and sabinene) was administered daily to mice, rats, or hamsters during gestation. When this data is combined with the fact that no adverse effects were observed to the reproductive organs in a 28-day study with camphene at dose levels up to 250 mg/kg bw/day, it is concluded that bicyclic terpene hydrocarbons including alpha-pinene and beta-pinene are not reproductive toxicants

Two ninety day inhalation studies have been performed for alpha-pinene in which a full complement of male and female sex organs and tissues were subjected to histopathological examination. Both studies reported no microscopic changes that could be associated with exposure to the test substance. Taking into account the lack of any effects to females in an earlier teratology study, the absence of any maternal or developmental effects in a reproductive/developmental study of a pinene-based oil and for a structurally related monoterpene hydrocarbon, myrcene, it can be concluded that the members of this category show no significant reproductive or developmental toxicity

Developmental toxicity: Based on the NOAELs for maternal and developmental toxicity in studies with camphene (250 and 1000 mg/kg bw/day) and a terpene hydrocarbon mixture containing alpha- and beta-pinene and camphene (688 mg/kg bw/day), and the lack of any signs of maternal or developmental toxicity in mice,

rats, or hamsters given 260 to 600 mg/kg bw/day of a mixture composed primarily (>80%) of alpha- and beta-pinene and sabinene, it is concluded that bicyclic terpene hydrocarbons are not maternal or developmental toxicants.

Genotoxicity:

In vitro: In vitro genotoxicity assays available for alpha-pinene, beta-pinene and camphene demonstrate that these substances have a little, if any, genotoxic potential. In standard Ames assays of alpha-pinene, beta-pinene and camphene, Salmonella typhimurium strains TA97, TA98, TA100, TA1535, TA1537, and TA1538 provided no evidence of mutagenicity at any dose tested.

In vivo: Based on the lack of any evidence of genotoxicity in numerous in vitro assays with and without metabolic activation, it is unlikely that any of these bicyclic terpenes would exhibit a significant genotoxic potential in vivo.

d-Limonene is readily absorbed by inhalation and ingestion. Dermal absorption is reported to be lower than by the inhalation route. d-Limonene is rapidly distributed to different tissues in the body, readily metabolised and eliminated primarily through the urine.

Limonene exhibits low acute toxicity by all three routes in animals. Limonene is a skin irritant in both experimental animals and humans. Limited data are available on the potential to cause eye and respiratory irritation. Autooxidised products of d-limonene have the potential to be skin sensitisers. Limited data are available in humans on the potential to cause respiratory sensitisation. Autooxidation of limonene occurs readily in the presence of light and air forming a variety of oxygenated monocyclic terpenes. Risk of skin sensitisation is high in situations where contact with oxidation products of limonene occurs.

Renal tumours induced by limonene in male rats is thought to be sex and species specific and are not considered relevant to humans. Repeated exposure affects the amount and activity of liver enzymes, liver weight, blood cholesterol levels and bile flow in animals. Increase in liver weight is considered a physiological adaptation as no toxic effects on the liver have been reported. From available data it is not possible to identify an NOAEL for these effects. Limonene is neither genotoxic or teratogenic nor toxic to the reproductive system.

GUM TURPENTINE:

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (human) LDLo: 1748 mg/kg
Unreported (man) LDLo: 441 mg/kg
Oral (woman) TDLo: 560 mg/kg
Oral (rat) LD50: 5760 mg/kg
Inhalation (human) TCLo: 175 ppm

IRRITATION

Eye (human): 175 ppm

- Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not

KCB GUM TURPENTINE

Hazard Alert Code:
MODERATE

Chemwatch Material Safety Data Sheet (REVIEW)

Revision No: 2.0

Chemwatch 23-0381

Issue Date: 21-Feb-2010

CD 2010/1

simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

For bicyclic terpenes:

Acute toxicity: The literature abounds with clinical reports of accidental and intentional acute poisoning with pinene-based turpentine.

Rat oral LD50 values are available for alpha-pinene, beta-pinene, camphene and turpentine oil and indicate these materials to be very low in oral acute toxicity with LD50 values in the range from 3388 mg/kg to greater than 5000 mg/kg. Rabbit dermal LD50 values similarly indicate very low toxicities with values greater than the limit doses of 2000 or 5000 mg/kg.

Acute inhalation toxicity has been measured in different animal species. The acute LC50 was reported to be 13,500 mg/m³ in rats, 13,500 mg/m³ in guinea pigs, and 9000 mg/m³ in mice. The acute inhalation LC50 of commercial grade turpentine in Wistar rats is reported to be in the range of 12,000-20,000 mg/m³ for 1 to 6 hour exposures and the LC50 for a 2-hour exposure in Swiss-Webster mice is 29,000 mg/m³. Based on these results the acute oral, dermal, and inhalation toxicities of bicyclic terpene hydrocarbons is concluded to be low.

Repeat dose toxicity: A 28-day repeat dose study has been performed with camphene according to an OECD Guideline 407 in both sexes of Wistar rats. Animals of both sexes at the 1000 mg/kg bw/day dose exhibited vacuolization of hepatocytes and increase liver weights. Male rats also exhibited alpha-2-microglobulin-type nephrotoxicity at all dose levels.

Subsequent investigations have shown that the alpha-2-microglobulin nephropathy found in the F344/N male rat does not develop in mammals that do not express the hepatic form of alpha-2-microglobulin

(e.g. other strains of rats, mice, dogs, humans). Therefore, the nephrotoxicity observed in the camphene study in male F344 rats is not relevant to the human health risk assessment. Based on liver toxicity, the NOAEL for this study is concluded to be 250 mg/kg bw/day

Reproductive toxicity:

In the a-animal species study, no reproductive effects were observed when dose levels of up to 260 to 600 mg/kg bw of an essential oil predominantly composed of bicyclic terpene hydrocarbons (alpha-pinene, beta-pinene, and sabinene) was administered daily to mice, rats, or hamsters during gestation. When this data is combined with the fact that no adverse effects were observed to the reproductive organs in a 28-day study with camphene at dose levels up to 250 mg/kg bw/day, it is concluded that bicyclic terpene hydrocarbons including alpha-pinene and beta-pinene are not reproductive toxicants

Two ninety day inhalation studies have been performed for alpha-pinene in which a full complement of male and female sex organs and tissues were subjected to histopathological examination. Both studies reported no microscopic changes that could be associated with exposure to the test substance. Taking into account the lack of any effects to females in a earlier teratology study, the absence of any maternal or developmental effects in a reproductive/developmental study of a pinene-based oil and for a structurally related monoterpene hydrocarbon, myrcene, it can be concluded that the members of this category show no significant reproductive or developmental toxicity

Developmental toxicity: Based on the NOAELs for maternal and developmental toxicity in studies with camphene (250 and 1000 mg/kg bw/day) and a terpene hydrocarbon mixture containing alpha- and beta-pinene and camphene (688 mg/kg bw/day), and the lack of any signs of maternal or developmental toxicity in a mice,

rats, or hamsters given 260 to 600 mg/kg bw/day of a mixture composed primarily (>80%) of alpha- and beta-pinene and sabinene, it is concluded that bicyclic terpene hydrocarbons are not maternal or developmental toxicants.

Genotoxicity:

In vitro: In vitro genotoxicity assays available for alpha-pinene, beta-pinene and camphene demonstrate that these substances have a little, if any, genotoxic potential. In standard Ames assays of alpha-pinene, beta-pinene and camphene, Salmonella typhimurium strains TA97, TA98, TA100, TA1535, TA1537, and TA1538 provided no evidence of mutagenicity at any dose tested.

In vivo:

Based on the lack of any evidence of genotoxicity in numerous in vitro assays with and without metabolic activation, it is unlikely that any of these bicyclic terpenes would exhibit a significant genotoxic potential in vivo.

d-Limonene is readily absorbed by inhalation and ingestion. Dermal absorption is reported to be lower than by the inhalation route. d-Limonene is rapidly distributed to different tissues in the body, readily metabolised and eliminated primarily through the urine.

Limonene exhibits low acute toxicity by all three routes in animals. Limonene is a skin irritant in both experimental animals and humans. Limited data are available on the potential to cause eye and respiratory irritation. Autooxidised products of d-limonene have the potential to be skin sensitisers. Limited data are available in humans on the potential to cause respiratory sensitisation. Autooxidation of limonene occurs readily in the presence of light and air forming a variety of oxygenated monocyclic terpenes. Risk of skin sensitisation is high in situations where contact with oxidation products of limonene occurs.

Renal tumours induced by limonene in male rats is thought to be sex and species specific and are not considered relevant to humans. Repeated exposure affects the amount and activity of liver enzymes, liver weight, blood cholesterol levels and bile flow in animals. Increase in liver weight is considered a physiological adaptation as no toxic effects on the liver have been reported. From available data it is not possible to identify an NOAEL for these effects. Limonene is neither genotoxic or teratogenic nor toxic to the reproductive system.

KCB GUM TURPENTINE

Hazard Alert Code:
MODERATE

Chemwatch Material Safety Data Sheet (REVIEW)

Revision No: 2.0

Chemwatch 23-0381

Issue Date: 21-Feb-2010

CD 2010/1

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

GUM TURPENTINE:

KCB GUM TURPENTINE:

- DO NOT discharge into sewer or waterways.
- For limonenes

Atmospheric fate: Due to the high volatility of limonene the atmosphere is expected to be the major environmental sink for this chemical where it is expected to undergo gas-phase reactions with photochemically produced hydroxyl radicals, ozone and nitrate radicals. Calculated lifetimes for the reaction of d-limonene with photochemically produced hydroxyl radicals range from 0.3-2 h based on experimentally determined rate constants. The oxidation of limonene may contribute to aerosol and photochemical smog formation.

Calculated lifetimes for the night-time reaction of d-limonene with nitrate radicals range from 0.9 to 9 minutes. The daytime atmospheric lifetime of d-limonene is estimated to range from 12 to 48 min. depending upon local hydroxyl rate and ozone concentrations. Products produced from hydroxy radical reaction with limonene are 4-acetyl-1-methylcyclohexene, a keto-aldehyde, formaldehyde, 3-oxobutanal, glyoxal and a C10 dicarbonyl. The same carbonyls, along with formic acid and C8 and C9 carboxylic acids, may form in reactions with ozone. Ozonolysis of limonene may also lead to the formation of hydrogen peroxide and organic peroxides, which have various toxic effects on plant cells and may damage forests.

Products of ozonolysis include bis(hydroxymethyl)peroxide, a precursor to hydroxymethyl hydroperoxide and hydrogen peroxide. The reaction of d-limonene with ozone in the dark results in the formation of 4-acetyl-1-methylcyclohexene and formaldehyde. Reactions with nitrogen oxides produce aerosol formation as well as lower molecular weight products such as formaldehyde, acetaldehyde, formic acid, acetone and peroxyacetyl nitrate.

Terrestrial fate: When released to the ground limonene is expected to have low to very low mobility in soil based on its physicochemical properties. The soil adsorption coefficient (Koc) calculated on the basis of solubility (13.8 mg/l, 25 C) and the log octanol/ water partition coefficient (4.23) ranges from 1030 and 4780. The Henry's law constant indicates that limonene will rapidly volatilise from both dry and moist soil; however its absorption to soil may slow the process.

Aquatic fate: In the aquatic environment, limonene is expected to evaporate to a significant extent owing to its high volatility. The estimated half-life for volatilisation of limonene from a model river (1 m deep, flow 1 m/s and wind speed 3 m/s) is 3.4 h. Some limonene is expected to absorb to sediment and suspended organic matter.

Biodegradation and bioaccumulation: Limonene does not have functional groups for hydrolysis and its cyclohexene ring and ethylene group are known to resist hydrolysis. Therefore, hydrolysis of limonene is not expected in terrestrial or in aquatic environments. The hydrolytic half-life of d-limonene is estimated to be >1000 days. Biotic degradation of limonene has been shown with some species of microorganisms such as *Penicillium digitatum*, *Corynespora cassiicola*, *Diplodia gossypina* and a soil strain of *Pseudomonas* sp (SL strain). Limonene is readily biodegradable (41-98% degradation by biological oxygen demand in 14 d) under aerobic conditions in a standard test (OECD 301 C "Modified MITI Test (1)", OECD, 1981a; MITI, 1992). Also in a test simulating aerobic sewage treatment (OECD 303 A "Simulation Test - Aerobic Sewage Treatment: Coupled Units Test"; OECD, 1981b), limonene disappeared almost completely (>93.8%) during 14 days of incubation.

Biodegradation has been assessed under anaerobic conditions; there was no indication of any metabolisms, possibly because of the toxicity to micro-organisms.

The bioconcentration factor, calculated on the basis of water solubility and the log octanol/ water partition coefficient (log Kow) is 246-262, suggesting that limonene may bioaccumulate in fish and other aquatic species.

Ecotoxicity: Technical limonene is practically nontoxic to birds on a subacute dietary basis, and is slightly toxic to freshwater fish and invertebrates on an acute basis.

for d-limonene:

LD50 *Colinus virginianus* (Bobwhite quail, 16 weeks old) oral >2000 mg/kg

LC50 *Colinus virginianus* (Bobwhite quail, 10 day old) dietary >5620 ppm/8 days

LC50 *Colinus virginianus* (Bobwhite quail, 14 day old) dietary >5000 ppm/8 days

LC50 *Anas platyrhynchos* (Mallard duck, 14 day old) dietary >5000 ppm/8 days

LC50 *Oncorhynchus mykiss* (Rainbow trout) 80 ppm/96 hr (95% confidence limit: 71.4-88.7 ppm); static /92% AI formulated product

LC50 *Oncorhynchus mykiss* (Rainbow trout) 568 ppm/96 hr (95% confidence limit: 437-852 ppm); static /4.0% AI formulated product

EC50 *Daphnia magna* (Water flea, <24 hr old; intoxication, immobilization) 17 ppm/48 hr (95% confidence limit: 11-33 ppm); static /4.0% AI formulated product

LC50 *Pimephales promelas* (Fathead minnow) 966 ppm/96 hr (95% confidence limit: 740-1652 ppm); static /4.0% AI formulated product

LC50 *Pimephales promelas* (Fathead minnow) 38.5 mg/L/96 hr; flow through /from table/ LC50

Leuciscus idus (Golden orfe) 32 mg/L/48 hr /Conditions of bioassay not specified in source examined

The acute toxicity of d-limonene ranges from slight to high for aquatic organisms. The lowest acute toxicity values (EC50 or LC50) identified were approximately 0.4 mg/litre for *Daphnia* (US EPA, 1990b) and 0.7 mg/litre for fish (US EPA, 1990a,b). The no-observed-effect concentration (NOEC) for

green algae is approximately 4 mg/litre (US EPA, 1990a). The acute toxicity (EC50 or LC50) of dipentene to *Daphnia* and fish is about 50-70 times lower than that for d-limonene (US EPA, 1990b). No studies were identified on the chronic toxicity of limonene to aquatic organisms.

■ Substances containing unsaturated carbons are ubiquitous in indoor environments. They result from many sources (see below). Most are reactive with environmental ozone and many produce stable products which are thought to adversely affect human health. The potential for surfaces in an enclosed space to facilitate reactions should be considered.

Source of unsaturated substances	Unsaturated substances (Reactive Emissions)	Major Stable Products produced following reaction with ozone.
Occupants (exhaled breath, ski oils, personal care products)	Isoprene, nitric oxide, squalene, unsaturated sterols, oleic acid and other unsaturated fatty acids, unsaturated oxidation products	Methacrolein, methyl vinyl ketone, nitrogen dioxide, acetone, 6MHQ, geranyl acetone, 4OPA, formaldehyde, nonanol, decanal, 9-oxo-nonanoic acid, azelaic acid, nonanoic acid.
Soft woods, wood flooring, including cypress, cedar and silver fir boards,	Isoprene, limonene, alpha-pinene, other terpenes and sesquiterpenes	Formaldehyde, 4-AMC, pinoaldehyde, pinic acid, pinonic acid, formic acid, methacrolein, methyl vinyl ketone, SOAs

KCB GUM TURPENTINE

Hazard Alert Code:
MODERATE

Chemwatch Material Safety Data Sheet (REVIEW)

Revision No: 2.0

Chemwatch 23-0381

Issue Date: 21-Feb-2010

CD 2010/1

houseplants		including ultrafine particles
Carpets and carpet backing	4-Phenylcyclohexene, 4-vinylcyclohexene, styrene, 2-ethylhexyl acrylate, unsaturated fatty acids and esters	Formaldehyde, acetaldehyde, benzaldehyde, hexanal, nonanal, 2-nonenal
Linoleum and paints/polishes containing linseed oil	Linoleic acid, linolenic acid	Propanal, hexanal, nonanal, 2-heptenal, 2-nonenal, 2-decenal, 1-pentene-3-one, propionic acid, n-butyric acid
Latex paint	Residual monomers	Formaldehyde
Certain cleaning products, polishes, waxes, air fresheners	Limonene, alpha-pinene, terpinolene, alpha-terpineol, linalool, linalyl acetate and other terpenoids, longifolene and other sesquiterpenes	Formaldehyde, acetaldehyde, glycoaldehyde, formic acid, acetic acid, hydrogen and organic peroxides, acetone, benzaldehyde, 4-hydroxy-4-methyl-5-hexen-1-al, 5-ethenyl-dihydro-5-methyl-2(3H)-furanone, 4-AMC, SOAs including ultrafine particles
Natural rubber adhesive	Isoprene, terpenes	Formaldehyde, methacrolein, methyl vinyl ketone
Photocopier toner, printed paper, styrene polymers	Styrene	Formaldehyde, benzaldehyde
Environmental tobacco smoke	Styrene, acrolein, nicotine	Formaldehyde, benzaldehyde, hexanal, glyoxal, N-methylformamide, nicotinaldehyde, cotinine
Soiled clothing, fabrics, bedding	Squalene, unsaturated sterols, oleic acid and other saturated fatty acids	Acetone, geranyl acetone, 6MHO, 40PA, formaldehyde, nonanal, decanal, 9-oxo-nonanoic acid, azelaic acid, nonanoic acid
Soiled particle filters	Unsaturated fatty acids from plant waxes, leaf litter, and other vegetative debris; soot; diesel particles	Formaldehyde, nonanal, and other aldehydes; azelaic acid; nonanoic acid; 9-oxo-nonanoic acid and other oxo-acids; compounds with mixed functional groups (=O, -OH, and -COOH)
Ventilation ducts and duct liners	Unsaturated fatty acids and esters, unsaturated oils, neoprene	C5 to C10 aldehydes
"Urban grime"	Polycyclic aromatic hydrocarbons	Oxidized polycyclic aromatic hydrocarbons
Perfumes, colognes, essential oils (e.g. lavender, eucalyptus, tea tree)	Limonene, alpha-pinene, linalool, linalyl acetate, terpinene-4-ol, gamma-terpinene	Formaldehyde, 4-AMC, acetone, 4-hydroxy-4-methyl-5-hexen-1-al, 5-ethenyl-dihydro-5-methyl-2(3H) furanone, SOAs including ultrafine particles
Overall home emissions	Limonene, alpha-pinene, styrene	Formaldehyde, 4-AMC, pinonaldehyde, acetone, pinic acid, pinonic acid, formic acid, benzaldehyde, SOAs including ultrafine particles

Abbreviations: 4-AMC, 4-acetyl-1-methylcyclohexene; 6MHQ, 6-methyl-5-heptene-2-one, 4OPA, 4-oxopentanal, SOA, Secondary Organic Aerosols

Reference: Charles J Weschler; Environmental Health Perspectives, Vol 114, October 2006.

■ Terpenes such as limonene and isoprene contribute to aerosol and photochemical smog formation. Emissions of biogenic hydrocarbons, such as the terpenes, to the atmosphere may either decrease ozone concentrations when oxides of nitrogen are low or, if emissions take place in polluted air (i.e containing high concentrations of nitrogen oxides), leads to an increase in ozone concentrations. Lower terpenoids can react with unstable reactive gases and may act as precursors of photochemical smog therefore indirectly influencing community and ecosystem properties.

Complex chlorinated terpenes such as toxaphene (a persistent, mobile and toxic insecticide) and its degradation products, were produced by photoinitiated reactions in an aqueous system, initially containing limonene and other monoterpenes, simulating pulp bleach conditions

The reactions of ozone with larger unsaturated compounds, such as the terpenes can give rise to oxygenated species with low vapour pressures that subsequently condense to form secondary organic aerosol.

■ For bicyclic monoterpenes:

Photodegradation: The calculated photodegradation half-lives for the structurally defined materials in this group are in the range from 1.4 to 9.4 hours. These calculations are based on measured OH rate constants for alpha-pinene, beta-pinene, camphene and trans-pinane, measured ozone and NO₃ rate constants with the exception of trans-pinane.

Stability In Water: No hydrolysis is possible for any of the materials in this group. All are expected to be very stable in aqueous solution.

Biodegradation: Studies evaluating biodegradability are available for this group of substances using standard OECD Guideline protocols. Additional studies in soil horizons obtained from coniferous and deciduous forests provide a broader perspective on the biodegradation of bicyclic terpene hydrocarbons in the environment. Four studies on alpha-pinene showed limited biodegradability. The first, evaluated inherent biodegradability, and reported 37% biodegradation at 31 days; the second, evaluated ready biodegradability, and reported 38% biodegradation at 28 days; and a third, evaluated ready biodegradability using a mixture mainly of alpha and beta-pinene in a closed bottle test, reported very limited biodegradability. In the fourth experiment, a mixture of 50.9% alpha-pinene and 36.8% beta-pinene was concluded to be inherently biodegradable based on the results of a closed bottle Sturm test. The mixture was 52% biodegraded within 28 days, but there was no indication that biodegradation had ceased.

Very limited biodegradability was also reported for 3-carene and for camphene (less than 20%). In studies showing limited biodegradability, the authors concluded that the high vapor pressure and low water solubility of these substances led to volatilization of the test substance in the upper parts of the test vessel, thereby, limiting aerobic biodegradation.

Additional studies in extracts and slurries prepared from soils of coniferous and deciduous forest indicate rapid and complete biodegradation of alpha-pinene in a closed bottle test. Soil extracts from coniferous and hardwood watersheds were added to sealed flasks containing oxygen-saturated media that were preconditioned with alpha-pinene for 24 hours. alpha-Pinene underwent 100% biodegradation after approximately 8 days in acclimated medium and after day 15 in non-acclimated medium. The authors

KCB GUM TURPENTINE

Hazard Alert Code:
MODERATE

Chemwatch Material Safety Data Sheet (REVIEW)

Revision No: 2.0

Chemwatch 23-0381

Issue Date: 21-Feb-2010

CD 2010/1

concluded the pinene is completely degradable in extracts prepared from watershed soils of coniferous or deciduous forests.

Ecotoxicity:

Fish LC50 (96 h): fathead minnow 0.28 mg/l (alpha-pinene); 0.5 mg/l (beta-pinene); Brachydanio rerio 0.72 mg/l (camphene) (closed system flow through).

The calculated values for camphene, cis-pinane, dihydropinene, and l-alpha-pinene, are 0.62, 0.63, 0.63 and 0.28 mg/l, respectively. These values indicate that all of these materials and mixtures that are made up primarily of these substances, should have acute fish toxicities on the order of 0.5 mg/l.

Daphnia magna LC50 (48 h): 1.44 mg/l (alpha-pinene); 1.256 mg/l (beta-pinene)

The calculated values for camphene, cis-pinane, dihydropinene, and l-alpha-pinene, 0.79, 0.8, 0.8 and 0.22 mg/l, respectively, indicates that all of these materials and mixtures that primarily are made up of these substances, should all have acute aquatic invertebrate toxicities on the order of 1.0 mg/l.

The 96-hour calculated values for camphene, cis-pinane, dihydropinene, and l-alpha-pinene, 0.56, 0.57, 0.57 and 0.22 mg/l, respectively, indicates that all of these materials and mixtures that primarily are made up of these substances, should all have acute aquatic plant toxicity on the order of 0.5 mg/l.

■ Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

■ Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

KCB GUM TURPENTINE:

GUM TURPENTINE:

Section 13 - DISPOSAL CONSIDERATIONS

-
- Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction,
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE LIQUID

HAZCHEM:

3Y (ADG7)

ADG7:

Class or division:	3	Subsidiary risk:	None
UN No.:	1299	UN packing group:	III
Special provisions:	None	Packing Instructions:	None
Notes:	None	Limited quantities:	5 L

KCB GUM TURPENTINE

Hazard Alert Code:
MODERATE

Chemwatch Material Safety Data Sheet (REVIEW)

Revision No: 2.0

Chemwatch 23-0381

Issue Date: 21-Feb-2010

CD 2010/1

Portable tanks and bulk containers - Instructions:	T2	Portable tanks and bulk containers - Special provisions:	TP1
Packagings and IBCs - Packing instruction:	P001; IBC03; LP01	Packagings and IBCs - Special packing provisions:	None
Shipping Name: TURPENTINE			
Land Transport UNDG:			
Class or division:	3	Subsidiary risk:	None
UN No.:	1299	UN packing group:	III
Shipping Name: TURPENTINE			
Air Transport IATA:			
ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	1299	Packing Group:	III
Special provisions:	None		
Shipping Name: TURPENTINE			
Maritime Transport IMDG:			
IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1299	Packing Group:	III
EMS Number:	F-E,S-E	Special provisions:	None
Limited Quantities:	5 L		
Shipping Name: TURPENTINE			

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE

S5

REGULATIONS

Regulations for ingredients

gum turpentine (CAS: 9005-90-7,8006-64-2) is found on the following regulatory lists;

"Australia Hazardous Substances", "Australia Inventory of Chemical Substances (AICS)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

No data for KCB Gum Turpentine (CW: 23-0381)

Section 16 - OTHER INFORMATION

Ingredients with multiple CAS Nos

Ingredient Name	CAS
gum turpentine	9005-90-7, 8006-64-2

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 21-Feb-2010

Print Date: 2-Mar-2010